

## CABLE TIES

### HTB-SK

BarLok®-Cable Tie SimLok, simple and favourable



#### Highlights

- Temperature range  
- 40 °C up to 85 °C
- Good value
- Fast and simple handling
- Very flexible
- Self-extinguishing
- Excellent resistance against many chemicals
- Approval: UL

#### Dimensions

Art.-No. natural	Reference	Cable Tie (mm)		Bundle Diameter mm	Loop Tensile Strength min. kg	Packaging Pcs./Box	Big Bag Pcs.
		Length	Width				
Z80041	HTQ-SK-140	140	1,78	1,6 bis 30,1	8.16	5.000	50.000
Z80042	HTQ-SK-203	203	1,78	1,6 bis 50,8	8.16	2.000	20.000

#### Technical characteristics

Property	Test	Inspection requirements
Material	Polyamid 6.6, natural	
Thermal	Operating temperature Melting point	-40 °C - 85 °C natural ca. +250 °C
Chemical	Flammability	Self-extinguishing, Flammability rating: V-2

Created by: NH 03042020

We reserve the right to make product changes.

**RELIABLE, FLEXIBLE,  
CUSTOMER-ORIENTED**

**HEINRICH THULESIUS GMBH & CO. KG**  
Zum Panrepel 15, D-28307 Bremen, GERMANY



#### SERVICE

Tel: +49 (0) 421-4895-0  
Fax: +49 (0) 421-4895-225  
E-Mail: [info@thulesius.de](mailto:info@thulesius.de)  
[www.thulesius.de](http://www.thulesius.de)

**SUMITOMO  
ELECTRIC  
GROUP**