

CABLE TIES

HTB-SL, HTB-SD, HTB-ES

BarLok®-Cable Tie, Slim Line-, Standard- and Extra Heavy Duty Style



Highlights

- Temperature range
- 40 °C up to 85 °C
- High tensile strength in all designs
- Pre-curved tongue for easy assembly
- Self-extinguishing
- Excellent resistance against many chemicals
- Weatherproof in black
- Approval: UL, MIL, VG

Dimensions

Art.-No. natural	Reference *	Cable Tie (mm)		Bundle Diameter mm / max.	Loop Tensile Strength min. kg	MIL- Standard	VG- Approval
		Length	Width				
Z80007	HTB-SL-80	83	2.40	16	8.20	MS-3367-4	-
Z80003	HTB-SL-100	102	2.40	24	8.20	MS-3367-4	96212
Z80005	HTB-SL-140	140	3.30	32	13.6	MS-3367-5	96212
Z80077	HTB-SL-155	156	2.60	38	8.20	-	-
Z80013	HTB-SD-190	192	4.50	45	22.7	MS-3367-1	96212
Z80020	HTB-SL-200	205	2.40	54	8.20	MS-3367-4	-
Z80015	HTB-SD-200	204	3.30	54	13.6	MS-3367-5	96212
Z80047	HTB-SD-280	279	4.50	76	22.7	MS-3367-7	-
Z80056	HTB-SD-380	381	4.50	102	22.7	MS-3367-2	96212
Z80053	HTB-ES-370	368	6.40	102	54.4	MS-3367-3	96213

* ES = Extra Heavy Duty; SD = Standard; SL = SlimLine

Standard: natural; heat stabilized (black) version on request.

Created by: NH 03042020

We reserve the right to make product changes.

**RELIABLE, FLEXIBLE,
CUSTOMER-ORIENTED**

HEINRICH THULESIUS GMBH & CO. KG
Zum Panrepel 15, D-28307 Bremen, GERMANY



SERVICE

Tel: +49 (0) 421-48 95-0
Fax: +49 (0) 421-48 95-225
E-Mail: info@thulesius.de
www.thulesius.de

**SUMITOMO
ELECTRIC
GROUP**

CABLE TIES

HTB-SL, HTB-SD, HTB-ES

BarLok®-Cable Tie, Slim Line-, Standard- and Extra Heavy Duty Style

Technical characteristics

Property	Test	Inspection requirements
Material	Polyamid 6.6, natural Polyamid 6.6, weatherproof, black Polyamid 6.6, heat stabilized, black	
Thermal	Operating temperature Operating temperature Melting point	MIL-S 23190D and UL, -40 °C - 85 °C, natural und black MIL-S 23190D and UL, -40 °C - 105 °C, heat stabilized, black ca. +250 °C
Chemical	Flammability	Self-extinguishing, Flammability rating: V-2

Created by: NH 03042020

We reserve the right to make product changes.

**RELIABLE, FLEXIBLE,
CUSTOMER-ORIENTED**

HEINRICH THULESIUS GMBH & CO. KG
Zum Panrepel 15, D-28307 Bremen, GERMANY



SERVICE

Tel: +49 (0) 421-4895-0
Fax: +49 (0) 421-4895-225
E-Mail: info@thulesius.de
www.thulesius.de

**SUMITOMO
ELECTRIC
GROUP**